



**Features:**

- All edges chamfered
- Flat/no step jaws, also known as soft jaws. Can be machined to shape of the part
- They have industry standard hole pattern that fits most manufacturer's vises, including Kurt, Chick, TE-CO, Toolex, Palmgren and others

Length	Height	Thickness	Hole Center-to-C	Hole Center-to-B	Screw Size	Hole Diameter	C-Bore Dia	C-Bore Depth	Aluminum	Steel
4"	1-1/2"	1.00	2.500	.687	3/8"-16	.409	.608	.8"	6061-T6	1018
4"	1-1/2"	1.50	2.500	.687	3/8"-16	.409	.608	1.3"	6061-T6	1018
6"	2"	1.00	3.875	.937	1/2"-13	.532	.788	.75"	6061-T6	1018
6"	2"	1.25	3.875	.937	1/2"-13	.532	.788	1"	6061-T6	1018
6"	2"	1.50	3.875	.937	1/2"-13	.532	.788	1.25"	6061-T6	1018
6"	2"	2.00	3.875	.937	1/2"-13	.532	.788	1.75"	6061-T6	1018
6"	3"	2.00	3.875	.937	1/2"-13	.532	.788	1.75"	6061-T6	1018
8"	2"	1.50	3.875	.937	1/2"-13	.532	.788	1.25"	6061-T6	1018
8"	2-1/2"	1.00	4.750	1.220	5/8"-11	.654	1.005	.675"	6061-T6	1018
8"	2-1/2"	2.00	4.750	1.220	5/8"-11	.654	1.005	1.55"	6061-T6	1018
10"	2	1.50	3.875	.937	1/2"-13	.532	.788	1.25"	6061-T6	1018